

DEVELOPED WITH THE AIM TO REDUCE THE COST OF DEPLOYING

A NETWORK FOR SMALL AND MEDIUM SIZE APPLICATIONS.

SL-Pico gateway is designed to meet the needs of a Plug & Play LoRaWAN™ private network solution.

It is enhanced with software layers developed by Sensing Labs and has a range up to 15 km.

KEY FEATURES • •

Compliant with many APIs and IoT / PLC platforms

Stand alone system: include SLcodec for messages decoding

Smart devices management: Status, reconfiguration, data history

Support up to 200 devices

Powerfull Embedded Graphical User Interface (GUI)

"Fleet management" Ready

Casing	Indoor (IP30)
Dimension	100.7 x x73.6 x 42.8mm
Weight	~250gr (1.01 lbs)
RF	868Mhz band (Power +14dBm / Sensitivity - 137dBm)
Operating Temperature	0°C to +50°C





SL GATEWAY-PICO IN ACTION









ECHNICAL FEATURES FOCUS

SPECIFICATION

DESCRIPTION

Operation system (OS)	Linux Debian
Connectivity	Ethernet (RJ45 plug) – GPRS modem
RF	868Mhz band (Power +14dBm / Sensitivity -137dBm)
Database	Storage of last 100 days data
Graphical User Interface	Light GUI for gateway configuration & management (available from local or remote access)
Security	Login/Password authentication (HTTP security) Firewall rules
Software maintenance	Easy update, Advanced configuration processes
Backup/Restore	Backup/restore for backup or massive deployment of SLgateway
CSV data export	Export all data or from selected days to CSV file
Remote access (VPN, DynDNS)	VPN configuration to your own OpenVPN server DynDNS configuration to your own dynDNS account
RF Range tester	Local LoRaWAN network coverage test dashboard
LoRaWan RF modem	Mono datarate (3 channels)
LoRaWan network server	ABP or OTAA activation mode PUBLIC or PRIVATE network type
LoRaWan application server	Application messages Decryption & Encryption Integrated Codecs for Senlab

Modbus

{ REST }

MOTE

HTTP

Callback

Data APIs access: